



# **AKRON DISPERSIONS, INC.**

## **MATERIAL SAFETY DATA SHEET**

Page 1 of 3

### **SECTION 1 PRODUCT IDENTIFICATION & EMERGENCY INFORMATION**

PRODUCT NAME: **Bostex 759**

CHEMICAL NAME: Aqueous Mixture of p-Oriented Styrenated Diphenylamine(CAS# 68442-68-2),  
Di(Tridecyl)Thiodipropionate(CAS# 10595-72-9), Sodium Dodecylbenzene Sulfonate  
(CAS# 25155-30-0/68081-81-2)

MANUFACTURER: Akron Dispersions, Inc.  
3291 Sawmill Road P.O. Box 4195  
Akron, Ohio 44321

TELEPHONE NUMBER: (330)666-0045

EMERGENCY TELEPHONE NUMBER: (330)666-0045

FAX: (330)666-7842

### **SECTION 2 HAZARDOUS INGREDIENT INFORMATION**

None Known

### **SECTION 3 HAZARDS IDENTIFICATION**

Health Hazards(Acute and Chronic): Prolonged skin contact may cause irritation.

HMIS: Health-1 Flammability-0 Reactivity-0 Personal Protection-B

### **SECTION 4 FIRST AID MEASURES**

Eye Contact: Flush with large amounts of water for at least 15 minutes. Consult a physician if irritation persists.

Skin Contact: Wash affected area with soap and water. Consult a physician if irritation persists.

Inhalation: Remove to fresh air. If breathing is difficult, seek medical attention.

Ingestion: Seek immediate medical attention.

### **SECTION 5 FIRE & EXPLOSION HAZARD**

Flashpoint: N/D Flammable Limits: N/D

General Hazard: Wear MSHA-NIOSH approved Self-Contained Breathing Apparatus

Extinguishing Media: CO<sub>2</sub>, Dry Chemical, Waterspray, Foam

Decomposition Products Under Fire Conditions: Oxides of Carbon, Nitrogen, Sodium, and Sulfur, Hydrogen Sulfide

**SECTION 6 ACCIDENTAL RELEASE MEASURES**

Steps To Be Taken In Case Material Is Released Or Spilled: Absorb with inert material. Sweep, vacuum, or shovel into appropriate container.

**SECTION 7 HANDLING AND STORAGE**

Storage: Store in a cool, dry area.  
Storage Temperature: Above 32°F

**SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION**

OSHA Regulation 29CFR1910.1000 requires the following PEL Limits: N/D  
The ACGIH recommends the following Occupational Exposure Limit: N/D  
Personal Protection: Gloves, Goggles, and Apron recommended  
Ventilation: Local Exhaust

**SECTION 9 TYPICAL PHYSICAL & CHEMICAL PROPERTIES**

Product Appearance: White to Off-White Liquid

Boiling Point(°F): 212	Freezing Point(°F): 32
Vapor Pressure(@150°C): N/A	Specific Gravity(Approx.): N/D
Vapor Density: N/A	% Volatile by Volume: 50%
Solubility in Water: Miscible	Evaporation Rate: N/A
pH: 8-11	

**SECTION 10 STABILITY AND REACTIVITY DATA**

Stability: Stable  
Conditions To Avoid Instability: None Known  
Materials And Conditions To Avoid Incompatibility: Acids, Alkali, Oxidizing Materials, Rubber, Steel  
Hazardous Decomposition Products: Oxides of Carbon, Nitrogen, Sodium, and Sulfur, Hydrogen Sulfide  
Hazardous Polymerization: Will Not Occur  
Conditions To Avoid Hazardous Polymerization: None Known

**SECTION 11 TOXICOLOGICAL INFORMATION**

Carcinogenicity(NTP/IARC/OSHA): None.

**SECTION 12 ECOLOGICAL INFORMATION**

Not determined

**SECTION 13 DISPOSAL**

Waste Disposal Method: Dispose per Local, State, and Federal Regulations

**SECTION 14 TRANSPORT INFORMATION**

DOT: Not a DOT controlled material(United States).

**SECTION 15 REGULATORY INFORMATION**

TSCA: All ingredients of this product appear on the TSCA Inventory

SARA Title III-Section 313: This product does not contain a toxic chemical in excess of 1% of the mixture(0.1% if a listed carcinogen).

**SECTION 16 OTHER INFORMATION**

Prepared By: D. Hunsicker

Date: January 13, 2010

The information in this MSDS was compiled from sources which we believe are accurate and reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness. It is the user's responsibility to determine the suitability of any material for a specific purpose and adopt such safety precautions as may be necessary. We do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of, or in any way connected with the handling, storage, use, or disposal of this product.